

Cable Track Cable

S 99 *ECO*

continuously flexible SABIX®/PUR control cable with numbered cores



Aufdruck-Beispiel für S 99 *ECO* 09741215:
SAB BRÖCKSKES · D-VIERSEN · S 99 *ECO* 12x1,5mm² CE

Construction:

Conductor:	bare copper strands acc. to IEC 60228, VDE 0295, class 6
Insulation:	SABIX®
Colour code from 2 conductors:	black cores with consecutive numbers acc. to EN 50334 + VDE 0293-334, green-yellow earth wire from 3 cores
Stranding:	specially adjusted layering with non-woven tape over each layer
Wrapping:	non-woven tape
Sheath material:	PUR, TMPU acc. to EN 50363-10-2 + VDE 0207-363-10-2 with mat surface
Sheath colour:	black (RAL 9005)

Outstanding features:

- » anticapacitance
- » PWIS uncritical
(PWIS = paint-wetting impairment substances)
- » flexible at low temperatures
- » halogen-free
- » high abrasion resistance
- » small bending radius
- » small outer diameter

Salt water resistance:

Nominal voltage:	U ₀ /U 300/500 V
Testing voltage:	core/core 2000 V
Torsion angle:	± 60°/1 m
Min. bending radius	
fixed laying:	3 x d
flexible application:	7,5 x d
Temperature range	
fixed laying:	-50/+90 °C
flexible application:	-40/+90 °C
Halogen-free:	acc. to IEC 60754-1 + VDE 0482-754-1
Oil resistance:	very good - TMPU acc. to EN 50363-10-2 + VDE 0207-363-10-2
Chem. resistance:	good against acids, alkalines, solvents, hydraulic liquids etc.
Continuous Flexibility:	very good
Sunlight resistance:	acc. to HD 605
Ozone resistance:	acc. to DIN EN 50396
Salt water resistance:	acc. to UL 1309
Absence of harmful substances:	gemäß RoHS-Richtlinie der Europäischen Union, siehe Kapitel N „Technische Daten“

item no.	no. of cores x cross section n x mm ²	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
multi-core cable unscreened					
09740505	5 x 0,50	0,16	5,4	24,0	43
09740705	7 x 0,50	0,16	6,4	33,6	60
09741205	12 x 0,50	0,16	7,6	57,6	86
09741805	18 x 0,50	0,16	9,0	86,4	125
09742505	25 x 0,50	0,16	11,0	120,0	173
09740207	2 x 0,75	0,16	4,9	14,4	30
09740307	3 x 0,75	0,16	5,2	21,6	37
09740407	4 x 0,75	0,16	5,6	28,8	48
09741807	18 x 0,75	0,16	10,6	129,6	184
09740210	2 x 1,00	0,16	5,1	19,2	35
09741210	12 x 1,00	0,16	9,1	115,2	146
09741810	18 x 1,00	0,16	11,0	172,8	226
09740215	2 x 1,50	0,16	5,7	28,8	47
09740315	3 x 1,50	0,16	6,0	43,2	63
09740415	4 x 1,50	0,16	6,5	57,6	78
09740515	5 x 1,50	0,16	7,3	72,0	99
09740225	2 x 2,50	0,16	6,7	48,0	67
09740525	5 x 2,50	0,16	8,5	120,0	140
09740361	3 x 10,0	0,21	13,6	288,0	394
09740162	1 x 16,0	0,21	7,9	153,6	169
09740163	1 x 25,0	0,21	9,3	240,0	250
09740164	1 x 35,0	0,21	11,1	336,0	356

Other dimensions and colours are possible on request.

item no.	no. of cores x cross section n x mm ²	largest single wire ø mm	outer-ø ± 5% mm	copper figure kg/km	cable weight ≈ kg/km
multi-core cable screened					
09841205	12 x 0,50	0,16	8,1	81,4	103
09840707	7 x 0,75	0,16	7,7	74,1	98
09842510	25 x 1,00	0,16	14,7	336,9	384
09840315	3 x 1,50	0,16	6,5	60,9	77
09840415	4 x 1,50	0,16	7,0	77,3	93
09845015	50 x 1,50	0,16	21,9	859,9	953
09840325	3 x 2,50	0,16	8,0	95,8	117

Other dimensions and colours are possible on request.

The S 99 *ECO* erhalten Sie mit

- » Multi-core cables:
Cross sections from 0.50 mm² to 50.0 mm²
- » Single conductors: Cross sections up to 300,0 mm²
- » Number of cores from 1 to 65